



310142

– L – STANDARD SEALS – Butt-Welding In According To BS-OD (ASTM A-270)

THREE-way ball valve 4 seals with “L” port
Drive: Inox lever
Connection: Butt-welding in according to BS-OD (ASTM A-270)
Flow: Full
Material: Aisi 316L (1.4404)
Measure: DN10 a DN100
Seals: Modified Virgin P.T.F.E.
Operating temperature: -20°C+170°C
Outer finish: Polished
On request:
Antistatic device ATEX:
II 2G Ex h IIC T4 Gb
II 2D Ex h IIIC T135°C Db
M.O.C.A. CE 1935/2004
• Seals made of:
PTFE with glass -20°C+170°C
PTFE with carbographite -20°C+180°C
PTFE with inox -20°C+200°C
UHMW High-molecular weight polyethylene -20°C+80°C


DIMENSIONS AND TECHNICAL DATA






DN	Ø A	B	L	G	C	H	PN	Kg	CODE AISI 316L
10	12,7 X 1,65	17	108	22,5	110	60	100	1,02	310142 6A710
15	19,05 X 1,65	18	118	26	110	65	100	1,32	310142 6B910
20	25,4 X 1,65	19	130	30	160	70	100	2.04	310142 6D710
25	25,4 X 1,65	19	140	35	160	80	64	2,87	310142 6D810
32	38,1 X 1,65	19	156	42,5	190	95	64	4,82	310142 6J910
40	38,1 X 1,65	19	172	50	190	110	64	7,20	310142 6K110
50	50,8 X 1,65	19	182	55	220	120	40	8,65	310142 6M810
65	63,5 X 1,65	21	196	80	285	130	40	10,62	310142 6R710
80	76,2 X 1,65	27	256	100	310	145	40	-	310142 6U510
100	101,6 X 2,11	27	286	120	310	160	16	-	310142 6X410


COMPONENTS AND MATERIALS




POS.	DENOMINATION	PCS	MAT.
1	Body	1	AISI 316L
2	Ball	1	AISI 316L
3	Sleeves	3	AISI 316L
4	Stem	1	AISI 316L
5	Ball Seals	4	PTFE Vergine Modificato
6	Sleeve Seals	3	PTFE
7	Stem Seal	1	PTFE
8	Stem Seal	1	PTFE
9	Stem or-Seal	1	FKM
10	Register ring	1	AISI 304L (303)
11	Nut	1	AISI 304L
12	Lever	1	AISI 304L
13	SCREW	1	AISI 304L
14	Handle	1	DUROPLAST (PF)

DIAGRAMS


Diagramma Pressione/Temperatura
Ptfe + Inox -20°,+200°C
Ptfe + Carbografite -20°,+180°C
Ptfe Vergine Modificato -20°,+170°C
Ptfe + Vetro -20°,+170°C
Uhmw -20°,+80°C
bar
°C


Pressure / Temperature Diagram
Ptfe + Inox -4°,+392°F
Ptfe + Carbographite -4°,+356°F
Ptfe Modified Virgin -4°,+338°F
Ptfe + Glass -4°,+338°F
Uhmw -4°,+176°F
psi
°F


DIAGRAMMA PORTATA/PERDITA DI CARICO E COEFFICIENTE NOMINALE Kv
FLOW/PRESSURE LOSS DIAGRAM AND Kv NOMINAL COEFFICIENT
Bar
DN10 - Kv=11
DN15 - Kv=20
DN20 - Kv=60
DN25 Kv=100
DN32 - Kv=130
DN40 - Kv=170
DN50 - Kv=280
DN65 - Kv=510
DN80 - Kv=770
DN100 - Kv=1200
mc/h