

# 373044

THREE-way ball valve three seals with “L” port
Drive: ISO 5211 - DIN 3337 flange for actuator
Connection: SMS female/female/female
Flow: full
Material: Aisi 304L - 316L
Measure: from DN 65 to DN 100
Seals: virgin P.T.F.E.
Operating temperature: -20°C +160°C
Outer finish: polished

## On request

Antistatic device ATEX (Directive 94/9/EC)
• DIN FEMALE connection
• DIN male connection
• Seals made of:
P.T.F.E. with glass
P.T.F.E. with carbographite
High-molecular weight polyethylene

| SMS | DN | Rd | L | I | H | PN | Kg | ISO-DIN | Ø_A | B | Ø_CXO | QU. | D | E | F | n4 bolts | NM | CODE AISI 304L | CODE AISI 316L |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 63 | 65 | 85 x 1/6" | 196 | 21 | 101,5 | 6 | | F.07 | 90 | 12 | 55x4 | 17 | 15 | 70 | 9 | M8x20 | 60 | 373044 44410 | 373044 64410 |
| 63 | 65 | 85 x 1/6" | 196 | 21 | 101,5 | 6 | | F.10 | 125 | 12 | 70x4 | 22 | 18 | 102 | 11 | M10x25 | 60 | 373044 4441F | 373044 6441F |
| 76 | 65 | 98x1/6" | 196 | 21 | 101,5 | 6 | 9.72 | F.07 | 90 | 12 | 55x4 | 17 | 15 | 70 | 9 | M8x20 | 60 | 373044 44510 | 373044 64510 |
| 76 | 65 | 98x1/6" | 196 | 21 | 101,5 | 6 | 10.20 | F.10 | 125 | 12 | 70x4 | 22 | 18 | 102 | 11 | M10x25 | 60 | 373044 4451F | 373044 6451F |
| 76 | 80 | 98x1/6" | 256 | 20 | 116 | 6 | 18,20 | F.07 | 90 | 12 | 55x4 | 17 | 15 | 70 | 9 | M8x20 | 75 | 373044 44810 | 373044 64810 |
| 76 | 80 | 98x1/6" | 256 | 20 | 116 | 6 | 18.65 | F.10 | 125 | 12 | 70x4 | 22 | 18 | 102 | 11 | M10X25 | 75 | 373044 4481F | 373044 6481F |
| 104 | 100 | 125x1/4" | 286 | 20 | 131 | 6 | 28.20 | F.07 | 90 | 12 | 55x4 | 17 | 15 | 70 | 9 | M8x20 | 110 | 373044 45410 | 373044 65410 |
| 104 | 100 | 125x1/4" | 286 | 20 | 131 | 6 | 28.70 | F.10 | 125 | 12 | 70x4 | 22 | 18 | 102 | 11 | M10x25 | 110 | 373044 4541F | 373044 6541F |
| 101 | 100 | 132x1/6" | 286 | 25 | 131 | 6 | - | F.07 | 90 | 12 | 55x4 | 17 | 15 | 70 | 9 | M8x20 | 110 | 373044 45510 | 373044 65510 |
| 101 | 100 | 132x1/6" | 286 | 25 | 131 | 6 | - | F.10 | 125 | 12 | 70x4 | 22 | 18 | 102 | 11 | M10x25 | 110 | 373044 4551F | 373044 6551F |

* Maximum break-out torque in Nm